# For sliding gates weighing up to 600kg.

Electromechanical gear motor surface mounted, also in 24Vdc version with magnetic encoder for gates up to 400kg.

Two versions with incorporated control unit and anti-crush safety feature for gates weighing up to 600kg, 230Vac: electronic clutch (RO1000); electric clutch (RO1010).

Long lasting and noiseless operation: metal and bronze alloy gears.

Easy maintenance thanks to the pull-out terminal boards.

Easy to install: externally mounted, with sturdy, user-friendly plate.

Functionality and safety: opto-insulated circuits protect the electronics against external disturbance; optional PIU board for expanding basic functions.

24Vdc version with magnetic encoder, perfect for intensive use

- easy programming by pressing a single button
- · clutch with anti-crush safety feature
- automatic memorization of limit switches in opening and closing with self-learning
- pause time programming; partial opening; slowdown during opening and closing
- the system will operate during a blackout by means of rechargeable batteries




The exclusive Nice release is easy to operate in all climates and is supplied complete with a safety switch to cut operation

The sturdy aluminium base, complete with practical external mounting

Code	Description	Pack/pallet
R01124	irreversible, 24Vdc, with incorporated control unit and with magnetic encoder	22
R01000	irreversible, 230Vac, with incorporated control unit, electronic clutch	22
R01010	irreversible, 230Vac, with incorporated control unit, electrical clutch	22

Technical specification	S	R01124	R01000	R01010
Power	(Vac 50Hz)	230		
Emergency power supply		24	-	
Power absorbed	(W)	120	400	
Current absorbed	(line) (A)	0.5	1.8	
Current absorbed	(motor) (A)	5	1.8	
Incorporated capacitor	(μF)	-	14	
Protection level (IP)		44		
Torque	(Nm)	10	17	
Speed	(m/s)	0.20	0.18	
Max thrust	(N)	330	560	
Max gate weight	(kg)	400	600	
Working temp. (°C Min/Max)		-20 ÷ +50		
Thermal cut-out	(°C)	-	140	
Insulation class		1		
Work cycle	(%)	80	30	
Dimensions (mm)		290x250x195		
Weight (kg)		10		



## Accessories for R01000 / R01010



ROA3 spare control unit, only card, for R01000



ROA4 spare control unit, only card, for RO1010



PIU expansion card for control unit

Pc/pack 1

### **Accessories for R01124**



ROA2 spare control unit, only card, for R01124



**CARICA** plug-in card for battery charger for use with A824

Pc/pack 1



B12-B 12V 6Ah batteries

Pc/pack 1



**BA3-A** Nice box for batteries

# **Common accessories**



L05 plastic rack 26x26x500mm, for gates weighing up to 400kg

Pc/pack 10



M4 25x20x1000mm slotted nylon rack with metal insert

Pc/pack 10



ROA7 M4 rack, zinc coated, 22x22x1000mm

Pc/pack 10



zinc coated with spacers and screws



Pc/pack 10



# TS

signboard

Pc/pack 1